



Environmental Equipment, Inc.

3634 Central Ave. · St. Petersburg, Florida 33711 · Phone 727-328-2818 · 800-RING-IMR · FAX 727/328-2826 · E-mail: Info@imrusa.com
www.imrusa.com

NEW COMBUSTIBLE GAS LEAK DETECTOR NEW CD200

CD200

The CD200 is small, easy to use and has a 18" long flexible gooseneck with a bright LED tip to find combustible gas leaks in tight areas.

- Adjustable tick rate to locate leaks quickly and easily
- Visual leak detection by LED indicators
- Separate user adjustable alarm for predetermined level detection
- Precision sensor detects even the smallest leaks
- Red LED located on the tip to illuminate the search area
- Fast response time (<2 seconds to 40%LEL)
- Small and light
- Earphone
- Impact resistant storage case

Partial list of gases detected:

Acetone, Alcohol, Ammonia, Butane, Gasoline, Halon, Hydrogen Sulfide, Industrial Solvents, Jet Fuel, Laquer Thinners, Naphta, Natural Gas, Propane, Select Refrigerants ... and more



SPECIFICATIONS

Power Supply	4 AA Alkaline batteries
Battery life	Approx. 12 hours
Sensor	Solid state semiconductor
Sensitivity	< 50ppm Methane
Warm-Up	Approx. 1 minute
Response time	< 2 seconds (to 40%LEL)
Recovery time	< 4 seconds (from 40%LEL)
Dimensions	8.6" x 3.1" x 2.3" (220x80x58 mm)
Gooseneck	18" (45cm)
Level Indicators	Audible: adjustable tick Visual: Six LEDs (green to red)

ACCESSORIES

Replacement Sensor
Replacement Sensor Cap
Earphones

IMR Environmental Equipment, Inc. reserves the right to adopt technical modifications without prior notice.

THE PRIDE OF THE COMPANY - MADE IN USA -

© Copyright 2003 IMR Environmental Equipment, Inc.