

IR-THERMOMETER

INF155



- MAX-Hold
- Auto Shut off after 15 seconds
- Holster
- Backlit display
- Over-molded handle with comfort grip

Temperature	-58°F to 750°F (-50°C to 400°C)
Resolution	0.1°F (0.1°C)
Accuracy	±2% of reading or 4°F (2°C) whichever is greater
Distance to spot	10:1
Operating range	32°F-122°F (0-50°C)
Emissivity	0.95
Battery	2x AAA-Batterien / typ. 18 hrs
Dimension	3.25" x 7" x 1,75" (8.3 x 17.8 x 4.4 cm)
Weight	7 oz. (200g)

INF185



- MIN/MAX/DIFF/AVG – Hold
- Auto Shut off after 15 seconds
- Worklight
- Contact probe input – Thermocouple Type K
- Adjustable emissivity
- Holster
- Hi/Lo - Alarm
- Backlit display
- Over-molded handle with comfort grip

Temperature	-76°F to 932°F (-60°C to 500°C)
Resolution	0.1°F (0.1°C)
Accuracy	± 1.8°F (1.0°C)
Thermocouple Type K	-83.2°F to 1999°F (-64°C to 1400°C)
Accuracy	±1% of reading or 1.8°F (1.0°C)
Distance to spot	12:1
Operating range	32°F-122°F (0-50°C)
Emissivity	Adjustable
Battery	2x AAA-Batterien / typ. 18 hrs
Dimension	3.25" x 7" x 1,75" (8.3 x 17.8 x 4.4 cm)
Weight	7 oz. (200g)

INF215



- MIN/MAX/DIFF/AVG - Hold
- Auto Shut off after 15 seconds
- UV - worklight
- Contact probe input – Thermocouple Type K
- Adjustable emissivity
- Holster
- Hi/Lo-Alarm
- Backlit display
- Over-molded handle with comfort grip

Temperature	-76°F to 1400°F (-60°C bis 760°C)
Resolution	0.1°F (0.1°C)
Accuracy	± 1.8°F (1.0°C)
Thermocouple Type K	-83.2°F to 1999°F (-64°C to 1400°C)
Accuracy	±1% of reading or 1.8°F (1.0°C)
Distance to spot	30:1
Operating range	32°F to 122°F (0-50°C)
Emissivity	Adjustable
Battery	2x AAA-Batterien / typ. 18 hrs
Dimension	3.25" x 7" x 1,75" (8.3 x 17.8 x 4.4 cm)
Weight	7 oz. (200g)